



Flexible flashing tape over flashing upstand

2.8x50mm hot dipped galvanised clout nails in to framing. Staggered @ 300 centers. (SS for Exposure Zone D)

16mm Single castellated timber head-batten  
\*See note

**NC226**  
Impervious barrier between batten & cladding

Cavity closer as per E2/AS1 (By others)

**NC134P**  
Pre-slotted base channel. Providing 2000mm<sup>2</sup> of ventilation per linear meter

5mm min gap

10mm min cover

Sealant for Very High to Extra High wind zones.

Proprietary penetration seal by others

Continuous sealant on PEF backing rod

Selected ventilation cowl

Flexible flashing tape applied to soaker and pipe

**NC246**  
Neoprene sealant tape

**NC248**  
Jamb flashing cap

**NC247**  
Jamb flashing base.

**NC227**  
Plastic soaker flashing. Base extends down in to base channel.

Stop-end tabbed up on both sides of head flashing

**Cavity batten note:**

- 20mm timber battens required for all Nu-Wall horizontal board installations
- Batten to have 15° slope for moisture egress
- Battens to all internal, external corners, jambs, and sills to be sized to 18mm to accommodate flashing build up
- 20 and 18mm single castellated battens are available directly from Nu Wall
- Proprietary Nu-Wall AliBat is available as an alternative when a structural non-combustible batten is required



Nu-Wall cladding horizontal on cavity  
Typical large pipe penetration with cowl

NW-HOC-022b.02

Drawn by: Nu-Wall	Date: 19/9/2024
Checked by: RL, GT	Scale: 1:2 @ A4

© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited