



Flexible flashing tape over flashing upstand

2x 2.8x50mm hot dipped galvanised clout nails in to nog framing @ 600 centres. (SS for Exposure Zone D) (2 nails per batten)

H3.2 vertical timber batten
*See note

Cavity closer as per E2/AS1 (By others)

Nu-Wall Fascia - can match wall cladding

NC134P
Pre-slotted base channel. Providing 2000mm² of ventilation per linear meter

Optional cavity closure:
Use standard 15mm head flashing see NW-VOC-029b

Soffit by others

NC247T + NC248
Termination flashing base and cap.

NC204
10g x 16mm csk Tek screw @ 600 centers through anti-crush packer (by others)

2.8x50mm hot dipped galvanised clout nails @ 600 centres. (SS for Exposure Zone D)

Ripped board

NC226
Impervious barrier between batten & cladding

Drained and vented cavity as per E2/AS1

NC203E
Fixing bracket @ 600mm centers

NC204
10g ss csk screws with 30mm min embedment

General note:
• Cladding fixings omitted for clarity

Cavity batten note:
• 20mm timber battens required for all Nu-Wall horizontal board installations
• Batten to have 15° slope for moisture egress
• Battens to all internal, external corners, jambs, and sills to be sized to 18mm to accommodate flashing build up
• 20 and 18mm single castellated battens are available directly from Nu Wall
• Proprietary Nu-Wall AliBat is available as an alternative when a structural non-combustible batten is required



	<p>Nu-Wall cladding horizontal on cavity Typical Nu-Wall fascia to soffit</p>	<p>NW-HOC-029.03</p>	
	<p>© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited</p>	<p>Drawn by: Nu-Wall</p>	<p>Date: 19/9/2024</p>
		<p>Checked by: RL, GT</p>	<p>Scale: 1:2 @ A4</p>